

# MAHI | DOWNLIGHT | BLACK

2015430103

nordlux®



Voltage (V): 230 Volt  
IP degree: IP65  
Class (Class 1, Class 2, Class 3):  
Class 2 (Double isolated)  
Socket type: LED Module

Primary material: Plastic  
Secondary material: Metal  
Colour of the glass: White  
Length of the cable (cm): 14.5  
Colour: Black

Height (cm): 4.5  
Mount directly into insulation:  
False

EAN: 5704924002755  
TUN: 2113369  
Item Number: 2015430103  
Pcs Per Master Carton: 3

Sales Box Height (cm): 13  
Sales Box Width (cm): 6.5  
Sales Box Depth (cm): 13  
Sales Box Volume m³: 0.0011  
Product net weight (kg): 0.159


Brightness of light (Lumen): 621  
Colour temperature (Kelvin): 3000  
Ra-value : 80  
Lifetime (hours): 20000  
Beam angle (°) : 100  
Candela (cd) (for directional  
lamp only): 310  
Energy class: F  
Actual watt (W): 8.5

- 3-step Moodmaker™ dimming by your regular wall switch • Inter-connectable
- 5-year LED guarantee

Mahi is a dimmable and inter connectable downlight that is due to its high degree of protection, IP65, both safe for bathroom use and integrated with the newest 3-step Moodmaker™ technology. The light can smoothly be dimmed and operated from the standard wall switch which means that the perfect lighting is only a few clicks away.

The Mahi downlight is a screwless connection with EasyConnect that is also equipped with a memory and reset function that saves your preferred light setting. The Moodmaker™ function will dim the brightness from 100% (621lm) to 55% (345lm) or 35% (230lm) by only a few simple clicks on the switch.


[www.nordlux.com](http://www.nordlux.com)



**Nordlux**  
2015430103

A	
B	
C	
D	
E	
F	
G	

**9**  
kWh/1000h



2019/2015