

MAHI | DOWNLIGHT | BRUSHED NICKEL

2015430155

nordlux®



Voltage (V): 230 Volt
IP degree: IP65
Class (Class 1, Class 2, Class 3):
Class 2 (Double isolated)
Socket type: LED Module

Primary material: Plastic
Secondary material: Metal
Colour of the glass: White
Length of the cable (cm): 13
Colour: Brushed Nickel

Height (cm): 4.5
Mount directly into insulation:
False

EAN: 5704924002779
TUN: 2113378
Item Number: 2015430155
Pcs Per Master Carton: 3

Sales Box Height (cm): 13
Sales Box Width (cm): 6.5
Sales Box Depth (cm): 13
Sales Box Volume m³: 0.0011
Product net weight (kg): 0.159


Brightness of light (Lumen): 621
Colour temperature (Kelvin): 3000
Ra-value : 80
Lifetime (hours): 20000
Beam angle (°) : 100
Candela (cd) (for directional
lamp only): 310
Energy class: F
Actual watt (W): 8.5

- 3-step Moodmaker™ dimming by your regular wall switch • Inter-connectable
- 5-year LED guarantee

Mahi is a dimmable and inter connectable downlight that is due to its high degree of protection, IP65, both safe for bathroom use and integrated with the newest 3-step Moodmaker™ technology. The light can smoothly be dimmed and operated from the standard wall switch which means that the perfect lighting is only a few clicks away.

The Mahi downlight is a screwless connection with EasyConnect that is also equipped with a memory and reset function that saves your preferred light setting. The Moodmaker™ function will dim the brightness from 100% (621lm) to 55% (345lm) or 35% (230lm) by only a few simple clicks on the switch.


www.nordlux.com



Nordlux
2015430155

A	
B	
C	
D	
E	
F	
G	

9
kWh/1000h



2019/2015