

KITCHENIO 1-KIT | SURFACE DOWNLIGHT | BRUSHED NICKEL

2015450155

nordlux®



Voltage (V): 230 Volt
IP degree: IP20
Class (Class 1, Class 2, Class 3):
Class 2 (Double isolated)
Bulb base: LED Module

Primary material: Plastic
Secondary material: Plastic
Color: Brushed Nickel

Height (cm): 2.1
Width (cm): 6.4
Length (cm): 6.4
Projection (cm): 2.1

EAN: 5704924002809
TUN: 2113381
Item Number: 2015450155
Pcs Per Master Carton: 3
Sales Box Height (cm): 6.8

Sales Box Width(cm): 6.8
Sales Box Depth (cm): 6.8
Sales Box Volume m³ : 0.0003
Product net weight (kg): 0.093

Brightness of light (Lumen): 170
Color Temperature (K): 3000-4000
Ra-value : 80
Lifetime (h): 25000
Beam Angle (°) : 110
Candela (cd) (for directional lamp only): 0
Energy Class: G
Actual Watt (W): 2

- 2-step Moodmaker™ (3000/4000 kelvin) by your regular wall switch • Parallel connection possible • Recessed and surface mounting possible
- Cable included (60 cm) • 5 year LED guarantee

The under-cabinet light Kitchenio is very flexible when it comes to installation as it can easily be recessed, or surface mounted using either screws or double tape. Especially, the included 2 or 4 wire connector block make Kitchenio ready for immediate installation. Equipped with both a 2-step Moodmaker and a memory and reset function enables you to change and save your favourite light setting.

The 2-step Moodmaker within the Kitchenio under cabinet light enables the possibility to obtain warm light by one single click and cold light by another click on the switch.

www.nordlux.com

ENERG

Nordlux
2015450155

A
B
C
D
E
F
G

3
kWh/1000h

2019/2015