


LEONIS IP65 1-KIT 2700K | DOWNLIGHT | BRUSHED NICKEL

2310016055

nordlux®



Voltage (V): 220-240 Volt
IP degree: IP65
Class (Class 1, Class 2, Class 3):
Class 2 (Double isolated)
Socket type: LED – Non-
replaceable light source
Dimmerable: False
Parallel connection: True

Primary material: Plastic
Secondary material: Plastic
Colour: Brushed nickel


Height (cm) : 3.6
Built In Spot Diameter (cm): 8.5
Mount directly into insulation:
False

EAN: 5704924015199
TUN: 2319285
Item Number: 2310016055

Pcs Per Master Carton: 3
Sales Box Height (cm): 13
Sales Box Width(cm): 13
Sales Box Depth (cm): 50
Sales Box Volume m³ : 0.0084
Product net weight (kg): 0.0766

Brightness of light (Lumen): 345
Colour temperature (Kelvin): 2700
Ra-value : 80
Lifetime (hours): 20000
Beam angle (°) : 110
Candela (cd) (for directional
lamp only): 0
Energy class: G
Actual watt (W): 4.5

- Suitable for the bathroom (IP65) • Easy installation
- Parallel connection possible • Long LED lifespan (20,000 hours)



Leonis is a simple downlight with a low installation height. With integrated LED, a plastic frame and a warm, white light (2700 kelvin).

Leonis is quick and easy to install, has a flexible cutting diameter (68–73/76mm) and allows for parallel connection.

The high protection rating (IP65) means Leonis is particularly suitable for the bathroom.

www.nordlux.com