

FREMONT 3-KIT IP65 4000K | DOWNLIGHT | BRUSHED STEEL

2310056032

nordlux®



Voltage (V): 220-240 Volt
IP degree: IP65
Class (Class 1, Class 2, Class 3):
Class 2 (Double isolated)
Socket type: LED – Non-
replaceable light source
Dimmerable: True
Parallel connection: True

Primary material: Metal
Secondary material: Plastic
Colour: Brushed steel

Height (cm) : 5.4
Built In Spot Diameter (cm): 8.5
Built In Width (cm): 17.2
Mount directly into insulation:
False

EAN: 5704924015229
TUN: 2319312
Item Number: 2310056032

Pcs Per Master Carton: 3
Sales Box Height (cm): 26.85
Sales Box Width(cm): 10.8
Sales Box Depth (cm): 6.8
Sales Box Volume m³ : 0.002
Product net weight (kg): 0.336

Brightness of light (Lumen): 380
Colour temperature (Kelvin): 4000
Ra-value : 80
Lifetime (hours): 25000
Beam angle (°) : 36
Candela (cd) (for directional
lamp only): 650
Energy class: F
Actual watt (W): 4.5

- Stepless dimming via a wall-mounted dimmer switch
- Suitable for the bathroom (IP65)
- Parallel connection possible
- Long LED lifespan (25,000 hours)

Fremont is a recessed LED spotlight with dimmable LEDs that can be tilted for a directional light.

Fremont has a long lifespan of 25,000 hours and emits a cold white light (4000 kelvin).

The high protection rating (IP65) means the spotlight is suitable for the bathroom.

www.nordlux.com

