


ROSALEE | DOWNLIGHT | BRASS

2410200135

nordlux®



Voltage (V): 220-240 Volt
IP degree: IP65/IP20
Class (Class 1, Class 2, Class 3):
Class 2 (Double isolated)
Socket type: LED – Non-replaceable light source
Parallel connection: True

Primary material: Aluminium
Secondary material: Plastic
Colour of the cable: Black
Length of the cable (cm): 30
Surface material of the cable: Plastic
Is the cable replaceable: False
Colour: Brass

IK degree: IK02
Height (cm) : 4.2
Width (cm): 8.6
Length (cm): 8.6
Mount directly into insulation: True

EAN: 5704924027567
TUN: 2550066
Item Number: 2410200135

Pcs Per Master Carton: 3
Sales Box Height (cm): 13
Sales Box Width(cm): 13
Sales Box Depth (cm): 7
Sales Box Volume m³ : 0.0012
Product net weight (kg): 0.2114

Brightness of light (Lumen): 600
Colour temperature (Kelvin): 2700/3000/4000
Ra-value : 80
Lifetime (hours): 50000
Beam angle (°) : 36
Candela (cd) (for directional lamp only): 1000
Energy class: D
Actual watt (W): 7

- High IP degree (IP65) • Can be mounted directly into insulation
- Low installation height • Choose between warm-, white- and cold light when mounting

Rosalee is an elegant downlight with a high IP degree. Choose between warm- (2700K), white- (3000K) or cold (4000K) light with the built in kelvin switch. The downlight can be mounted directly into insulation and has a very low installation height.

