


nordlux®



UNE 1-SPOT

Dessin: 45410034
Db: 1910006
Rustfrit stål
Edelstahl
Stainless steel
Rostfritt stål
Acier inoxydable



nordlux®



UNE 1-SPOT

by nordlux®

Suitable for outdoor use
Features

M

P

LED

0.6W

EXTENSION
FOR UNE 6-KIT
ONLY!

nordlux®



UNE 1-SPOT

by nordlux®

Suitable for outdoor use
Features

M

P

LED

0.6W

EXTENSION
FOR UNE 6-KIT
ONLY!

nordlux® 45410034

 This luminaire contains built-in LED lamps.

A++

A+

A

B

C

D

E

LED

The LED lamps cannot be changed in the luminaire.

874/2012



 **NO MERCURY**

Ra

>65

30000 HOURS



 3000 KELVIN



PLEASE NOTE
LED MODULE IS
FIXED IN LAMP

95% ϕ
warm up
< 2 sec
Light up:
< 0,5 sec

LED

0,6W

15000 ON/OFF

 120°

20 LUMEN

www.nordlux.com/safedisip/dk
www.nordlux.com/safedisip/de
www.nordlux.com/safedisip/uk
www.nordlux.com/safedisip/se
www.nordlux.com/safedisip/fr

FIXED LED



NO DRIVER INCLUDED

MAX 10 SPOTS FOR 1 DRIVER

Max. 100kg belastning
Max. 100Kg Gewicht
Max. 100kg load
Max. 100kg belastning
Charge max. en 100kg

IP67



230V





M/P






Klasse 3
Schutzklasse 3
Class 3
Klass (3)
Classe 3

Hukdiameter 2,5 cm
Einbaudiameter 2,5 cm
Hole diameter 2,5 cm
Håldiameter 2,5 cm
Diamètre de perçage 2,5 cm

Metal/Plast
Metal/Kunststoff
Metal/Plastic material
Metal/Plastik
Métal/Plastique

Egnet til udendørs brug
Geeignet für Außen
Suitable for outdoor
Lämplig för utomhusbruk
Indiqué pour usage extérieur



! Denmark skal udendørs lamper monteres af en autoriseret elektriker.
In Denmark, outdoor lightings must be mounted by an authorized electrician.
In Danmark muss Außenleuchten von einem autorisierten Elektriker montiert werden.
! Danmark skall utomhus lampor monteras av en auktoriserad elektriker.
Au Danemark les lampes pour usage extérieur doivent être montées par un installateur-électricien autorisé.

www.nordlux.com

Nordlux A/S · Karlsgavevej 8 · DK-9200 Aalborg SV



AAD: 24042017 RO

Height x Width x Depth COLOR BOX (CM)	NET WEIGHT COLOR BOX (KG)
9X9X9	0.03
GROSS WEIGHT COLOR BOX (KG)	VOLUME COLOR BOX (CBM)
0.095	0.001