nordlux®
47580132
This luminaire contains built-in LED lamps.
A++
A+
A
C
D
LED
The lamps cannot be changed in the luminaire.
874/2012
5,4cm
8,5cm
IP20
≥50mm
≥50mm
≥68mm
IP23
5~15mm
FREMONT
2700K | 3-KIT | 230 V
Dessin: 47580132
Db: 1975415
Børstet stål/Gebürsteter Edelstahl
Brushed Steel/Borstat stål
Acier brossé
LED 5,5W
PLEASE NOTE LED MODULE IS FIXED IN LAMP
15000 ON/OFF
345 LUMEN
20000 HOURS
IP23
FIXED LED
M/P
Metal/Plast
Metall/Kunststoff
Metal/Plastic material
Metall/Plastik
Métal/Plastique
230V
Indoor
Egnet til indendørs brug
Geeignet für Innen
Suitable for Indoor
Lämplig att användas inomhus
Indiqué pour usage intérieur
2700 KELVIN
instant FULL LIGHT
DER GRÜNE PUNKT
Dobbelt isoleret (kl 2)
Doppelte isolierung
Double insulation
Dubbel isolering
Double protection
Hg MERCURY
36°
Ra 80
Kipningsgrad: 12°
Schwenkbar bis: 12°
Angle of tilt: 12°
Lampans vridningsgrad: 12°
Degré de déversement: 12°
www.nordlux.com/safedisp/dk
www.nordlux.com/safedisp/de
www.nordlux.com/safedisp/uk
www.nordlux.com/safedisp/se
www.nordlux.com/safedisp/fr
Huldiameter 7,2 cm
Einbaudiameter 7,2 cm
Hole diameter 7,2 cm
Håldiameter 7,2 cm
Diámètre de percage 7,2 cm
www.nordlux.com
Nordlux A/S · Østre Havnegade 34 · 9000 Aalborg
5 701581 415980
Må ikke indbygges direkte i isolering
Nicht direkt in der Isolierung einbauen
Do not build directly into insulation
Får inte byggas direkt in i isoleringen
Pas directement dans l'isolement
Parallelforbindelse muligt
Parallelschaltung möglich
Parallel arranging possible
Möjligt atv parallellkoppla
Montage en paralléle possible
DIMMABLE
2700K
345 LUMEN
5 YEAR LED GUARANTEE
AAD: 24042018 YK
Height × Width × Depth COLOR BOX (CM)
30x11x7 CM
NET WEIGHT COLOR BOX (KG)
0.072 KG
GROSS WEIGHT COLOR BOX (KG)
0.468 KG
VOLUME COLOR BOX (CBM)
0.00231 CBM
437.50
110.00
70.00
110.00
69.00
377.00
瓦向