
## LEONIS 3-KIT 4000K | DOWNLIGHT | WHITE

nordlux®

49200101





Voltage (V): 220-240 Volt IP degree: IP65 Class (Class 1, Class 2, Class 3): Class 2 (Double isolated) Socket type: LED – Nonreplaceable light source Dimmerable: False Parallel connection: True

Primary material: Plastic Secondary material: Plastic

Colour: White

Height (cm) : 3.6
Built In Spot Diameter (cm): 8.5
Mount directly into insulation:
False

EAN: 5701581467187 TUN: 2298482 Item Number: 49200101 Pcs Per Master Carton: 3 Sales Box Height (cm): 26.85 Sales Box Width(cm): 10.8 Sales Box Depth (cm): 6.8 Sales Box Volume m³: 0.002 Product net weight (kg): 0.2298

Brightness of light (Lumen): 400 Colour temperature (Kelvin): 4000 Ra-value: 80

Lifetime (hours): 20000 Beam angle (°) : 360 Energy class: F Actual watt (W): 4.5

Suitable for the bathroom (IP65) • Easy installation
 Parallel connection possible • Long LED lifespan (20,000 hours)

Leonis is a simple downlight with a low installation height. With integrated LED, a plastic frame and a warm, white light (4000 kelvin).

Leonis is quick and easy to install, has a flexible cutting diameter (68–73/76mm) and allows for parallel connection.

The high protection rating (IP65) means Leonis is particularly suitable for the bathroom.

