DORADO 3-KIT DIM | DOWNLIGHT | NICKEL

nordlux®

49410155




Voltage (V): 230 Volt IP degree: IP65 Class (Class 1, Class 2, Class 3): Class 2 (Double isolated) Socket type: LED Module Dimmerable: True Parallel connection: True

Primary material: Metal Secondary material: Plastic Colour: Nickel Height (cm): 3.6 Built In Spot Diameter (cm): 8.5 Mount directly into insulation: False

EAN: 5701581471283 TUN: 2049785 Item Number: 49410155 Pcs Per Master Carton: 3 Sales Box Height (cm): 13 Sales Box Width(cm): 13 Sales Box Depth (cm): 11.5 Sales Box Volume m³ : 0.0019 Product net weight (kg): 0.474

Brightness of light (Lumen): 345 Colour temperature (Kelvin): 2700 Ra-value : 80 Lifetime (hours): 25000 Beam angle (°) : 100 Candela (cd) (for directional lamp only): 0 Energy class: E Actual watt (W): 4.7



 Stepless dimmable by wall dimmer • Suitable for humid areas (IP65) • Parallel connection possible
• Connector block included • 5-year LED guarantee

A classic round downlight with an integrated LED 345Im dimmable LED module. Dorado is quick and easy to mount via a screwless plug-in connection and a twist-lock system, and at the same time multiple downlights can be easily connected to each other.

The downlight emits a warm light of 2700 K, which makes it particularly suitable in the living room, the dining room or the bedroom. The high degree of IP makes the downlight ideal for humid environments such as the bathroom.

www.nordlux.com