

nordlux®

**MENTO**

Dessin: 75531001  
 Db: 1479991  
 Hvid/Weiss  
 White/Vit  
 Blanc/Wit



nordlux®

**360 Cd**

**Ra 80**

**50°**

**30000 HOURS**

**LED 4W**

**3000 KELVIN**

**15000 ON/OFF**

95% ∅ warm up < 1 sec  
 Light up: < 0,5 sec

**220 LUMEN**

[www.nordlux.com/safedis/dis/dk](http://www.nordlux.com/safedis/dis/dk)  
[www.nordlux.com/safedis/dis/de](http://www.nordlux.com/safedis/dis/de)  
[www.nordlux.com/safedis/dis/uk](http://www.nordlux.com/safedis/dis/uk)  
[www.nordlux.com/safedis/dis/se](http://www.nordlux.com/safedis/dis/se)  
[www.nordlux.com/safedis/dis/fr](http://www.nordlux.com/safedis/dis/fr)

**MENTO**

nordlux®

**MENTO**

Dessin: 75531001  
 Db: 1479991  
 Hvid/Weiss  
 White/Vit  
 Blanc/Wit

**LED M**

Dobbelt isoleret (M II)  
 Doppelte Isolierung  
 Double insulation  
 Dubbel isolering  
 Double protection

Metal  
 Metal  
 Metal  
 Metall  
 Métal

Afbryder  
 Schalter  
 Switch  
 Strömbrytare  
 Interrupteur

Ledningslængde: 180 cm  
 Kabellänge: 180 cm  
 Cord length: 180 cm  
 Sladd längd: 180 cm  
 Longueur de câble: 180 cm

[www.nordlux.com](http://www.nordlux.com)  
 Nordlux A/S · Østre Havnegade 34 · DK-9000 Ålborg

5 701581 285972