HELIX | GARDEN LIGHTING | GALVANIZED

nordlux®







Voltage (V): 230 Volt IP degree if the fixture includes two types of IP degree: IP44 Maximum compatible bulb wattage (W): 8W SMD LED Class (Class I, Class II, Class III): Class 2 (Double isolated) Lampholder type (eg, E27/E14, etc): GU10 Parallel connection possible?: True

Primary material: Galvanized steel Secondary material: Plastic Color of the Glass: Clear Color: Galvanized

Height (cm): 80 Base Dimention (cm): 15

EAN: 5701581248786 TUN: 1621980 Item Number: 77498031 Pcs Per Master Carton: 2 Sales Box Height (cm): 83.7 Sales Box Width(cm): 17.2 Sales Box Depth (cm): 17.2 Sales Box Volume m³ : 0.0248 Net weight of the luminiare (kg): 2.376

Useful Lumen (Im): 390 Color Temperature (K): 2700 Ra-value : 80 Lifetime (h): 15000 Spread Angle (°) (beam angle of luminaire): 36 Candela (cd) (for directional lamp only): 650

Retrofit GU10 bulbs • Can be mounted on Nordlux base unit
• Designed by Bønnelycke mdd • Retrofit GU10 bulbs

HELIX illuminates outdoor areas with its distinctive design. The screws are visible, and the finish exudes raw confidence. The actual light bulb is hidden from the eye. It comes from below and ensures indirect lighting, which is evenly distributed in the top part of the light. Design by Bønnelycke MDD.

The galvanised finish makes the light fixture resistant to the Nordic climate. We recommend light fixtures in galvanised steel for coastal areas. It is possible to purchase a base for pillar lighting appropriate for this product.

www.nordlux.com