



nordlux®

nordlux




**TILOS EFFECT**

Dessin: 96409934  
Db: 5384907  
Rustfrit stål  
Edelstahl  
Stainless steel  
Rostfritt stål  
Inox/Roestvrij staal



nordlux®



**BULB NOT INCLUDED**

**TILOS EFFECT**

nordlux®



**BULB NOT INCLUDED**

**TILOS EFFECT**

nordlux®









DESIGNED FOR OUTDOOR USE




nordlux®

**TILOS EFFECT**

Dessin: 96409934  
Db: 5384907


IP67		Dobbelt isoleret (M II) Doppelte Isolierung Double insulation Dubbel isolering Double protection Dubbels isolate
GU10		Parallelförbindbar muligt Parallelschaltung möglich Parallel arrangement possible Möjligt att parallellkoppla Montage en parallèle possible Paralleel aansluiten mogelijk
MAX 5W		Hukdiаметer 68-75mm Einbaudiаметer 68-75mm Höjdiameter 68-75mm Höjdiameter 68-75mm Diamètre de perçage 68-75mm Zaag maat 68-75mm
230V ~50Hz		Metal/Glas Metal/Glas Metal/Glas Metal/Werres Metaal/glas
		Max. 750 kg belastning Max. 750 Kg Gewicht Max. 750 kg load Max. 750 kg belastning Charge max. en 750 Kg Max. Belastung 750 Kg
		Egnet til udendørs brug Geeignet für Außen Suitable for outdoor Lämplig för utomhusbruk Indiqué pour usage extérieur Geschikt voor buiten



**BULB NOT INCLUDED**

**TILOS EFFECT**

[www.nordlux.com](http://www.nordlux.com)  
Nordlux A/S - Østre Havnegade 34 - DK-9000 Aalborg



5 1704924 005978

AAD: 20082020XY